



WS



NEW

0033

SCHLANGENBOHRER, 4-KANT, FORM JENNINGS JENNINGS PATTERN AUGER BIT MÈCHES TORSE JENNINGS

(DE) Ausführung: „DIN 6444; Mit Vierkantschaft; mit Gewindespitze, zweigängige Spirale, 2 Vorschneider, fein polierte Oberfläche“.

Verwendung: Mit einer 4-Backen Bohrwinde. Eingesetzt in Weich und Hartholz, wenn keine Bohrmaschine zur Verfügung steht oder man besonders feinfühlig bohren möchte. Nur für Handbetrieb. Durch die optimierte Scheidengeometrie ist ein „butterweiches“ einbohren möglich.

(EN) Characteristics: DIN 6444; Traditional square taper shank; fine screw thread tip for hardwoods, 2 cutting spurs, double flute spiral, polished surface.

Usage: For cutting through soft and hard wood. Fast clearing action preferred by furniture makers and crafts workers. The two cutting spurs cut the fibers of the wood as the screw thread tip pulls the bit through the wood. The traditional square taper shank fits two jaw braces. For manual operation only.

(FR) Caractéristiques : Selon DIN 6444; mèche polie à double spirale, 2 couteaux, 2 traçoirs, queue carrée et pointe à vis.

Utilisation : Mèche carrée pour perçage au vilebrequin dans des bois tendres et durs. Exclusivement réservée au perçage manuel pour des travaux de précision. Son angle d'affûtage, ses 2 couteaux et traçoirs facilitent un perçage sans effort.

Ø	NL	GL	S	EAN	ART.NR.
1/4"	4 5/16"	9"	4-kant	357193	003300635
5/16"	4 5/16"	9"	4-kant	357209	003300794
3/8"	4 5/16"	9"	4-kant	357216	003300952
1/2"	4 5/16"	9"	4-kant	357223	003301270
9/16"	4 5/16"	9"	4-kant	357230	003301428
5/8"	4 5/16"	9"	4-kant	357247	003301588
3/4"	4 5/16"	9"	4-kant	357254	003301905
7/8"	4 5/16"	9"	4-kant	357261	003302223
1"	4 5/16"	9"	4-kant	357278	003302540

