



PREMIUM ZAPFENSCHNEIDER PREMIUM TENON CUTTER MÈCHES À BOUCHONNER QUALITÉ PREMIÈRE

DE Ausführung: Präzisionsgeschliffene Schneidengeometrie aus hochlegiertem HSS, mehrschneidig, mit Peripherieschneide und zylindrischem Schaft. Bis Dm. 32 mm: Schaft 13x50mm. Ab Dm. 33mm: Schaft 16x50mm.

Verwendung: Zur Herstellung von hochqualitativen und glatten Zapfen, z.B. bei Handlaufverbindungen in der Treppenfertigung, oder zur Herstellung von Holzdübeln wie z.B. Astlochdübeln oder Schraubenabdeckungen. Durch optimierte Schneidengeometrie wenig Leistungsbedarf, speziell im Hartholz. Extra lange Lebensdauer. In Verwendung mit Forstnerbohrer und Kunstbohrer.

EN Characteristics: Precision-cut cutting edge geometry made of Highspeed Steel, multi-cut, with peripheral cutting edge and cylindrical shank. For diameter up to 32mm: shank 13x50mm. From diameter 33mm: shank 16x50mm.

Usage: For producing high-quality and smooth tenons, e.g. for hand rail junctions in making stairs or for the production of wood dowels, such as knothole dowels or screw covers. Due to optimized cutting edge geometry, low energy input required, especially in hardwood. Extremely long lifetime. Used with Forstner bits and hinge boring bits.

FR Caractéristiques: Multi-coupes, en acier HSS, la géométrie des couteaux affûtés de haute précision favorise une coupe sans efforts. Queue cylindrique de Ø 13 x 50 mm (à partir de Ø 32, queue de Ø 16 x 50 mm).

Utilisation: Outil professionnel de haute précision pour la fabrication de bouchons. Important : à utiliser impérativement avec nos mèches à façonner et sur une perceuse fixe (à colonne).

| Ø | NL | GL | S | Z | EAN | ART.NR. |
|----|-----|-----|----|---|---------------|-------------|
| 15 | 80 | 140 | 13 | 4 | 9002696282914 | 03600150001 |
| 20 | 80 | 140 | 13 | 4 | 9002696282921 | 03600200001 |
| 25 | 80 | 140 | 13 | 5 | 9002696282938 | 03600250001 |
| 30 | 80 | 140 | 13 | 5 | 9002696282945 | 03600300001 |
| 35 | 100 | 160 | 16 | 5 | 9002696282952 | 03600350001 |

| Ø | EAN | ART.NR. |
|----------------|---------------|-------------|
| 15-20-25-30-35 | 9002696282969 | 03600005K01 |

03601

