



DÜBELBOHRER MIT ZENTRIERSPITZE DOWEL DRILLS WITH CENTERING POINT MÈCHES À CHEVILLER AVEC POINTE DE CENTRAGE

DE Ausführung: Schneidkopf HW massiv, mit 2 Schneiden und angeschliffenen Vorschneider, Zentrierspitze, Zylinderschaft mit Spannfläche und Einstellschraube.

Verwendung: Zum Anfertigen ausrissfreier Bohrungen in Spanplatten und beschichteten Plattenwerkstoffen. Zum Bohren von Sacklöchern insbesondere Dübellöchern im Möbelbau. Auch zur Verwendung in Reduzierfutter. Drehzahl: 2500–9000 U/min. Vorschub: bis zu 4 m/min.

EN Characteristics: TCT, with center point, 2 cutters, 2 spurs, and cylindrical shank with flat and set screw. Right or left hand cutting. Other diameters and specification on request. 500M for Maffel.

Usage: For drilling smooth holes in high density woods, laminated boards and chipboards. For drilling blind holes in particular dowel holes in furniture. To use also in adapter chuck. 2500–9000 RPM. Feed rate: up to 4m/min.

FR Caractéristiques : Mèche avec tête au carbure monobloc, 2 coupes et traçoirs affûtés, une pointe de centrage, une queue cylindrique avec méplat et vis de réglage. 500M pour Maffel.

Utilisation : Pour un perçage sans éclats dans des panneaux stratifiés. Utilisable également avec des mandrins porte-mèches. Vitesse de rotation 2500-9000 t/min. Avancement : jusqu'à 4m/min.

Ø	NL	GL	S	SL	EAN	ART.NR.
3	27	57,5	10	27	9002696135845	5000300570
3	38	70	10	27	9002696340478	5000300700
4	27	57,5	10	27	9002696005223	5000400570
4	38	70	10	27	9002696034490	5000400700
5	27	57,5	10	27	9002696005247	5000500570
5	38	70	10	27	9002696005261	5000500700
6	27	57,5	10	27	9002696005285	5000600570
6	38	70	10	27	9002696034612	5000600700
7	27	57,5	10	27	9002696005308	5000700570
7	38	70	10	27	9002696034636	5000700700
8	27	57,5	10	27	9002696005346	5000800570
8	38	70	10	27	9002696005360	5000800700
10	27	57,5	10	27	9002696005407	5001000570
10	38	70	10	27	9002696034735	5001000700
12	27	57,5	10	27	9002696005421	5001200570
12	38	70	10	27	9002696034780	5001200700

rechtslaufend / right hand cutting / Rotation à droite

Ø	NL	GL	S	SL	EAN	ART.NR.
3	27	57,5	10	27	9002696136491	5010300570
3	38	70	10	27	9002696340492	5010300700
4	27	57,5	10	27	9002696005216	5010400570
4	38	70	10	27	9002696034926	5010400700
5	27	57,5	10	27	9002696005230	5010500570
5	38	70	10	27	9002696005254	5010500700
6	27	57,5	10	27	9002696005278	5010600570
6	38	70	10	27	9002696035046	5010600700
7	27	57,5	10	27	9002696005292	5010700570
7	38	70	10	27	9002696035060	5010700700
8	27	57,5	10	27	9002696005339	5010800570
8	38	70	10	27	9002696005353	5010800700
10	27	57,5	10	27	9002696005391	5011000570
10	38	70	10	27	9002696035169	5011000700
12	27	57,5	10	27	9002696005414	5011200570
12	38	70	10	27	9002696035213	5011200700

linkslaufend / left hand cutting / Rotation à gauche

500/501

